

TVLOGIC LVM-095 9" FULL-HD monitor

(業務請電 0922-270-380 林建鑫 暉欣科技有限公司 www.ws-tech.com.tw)



PRODUCT HIGHLIGHT

9" 1920x1080 (16:9) Native Resolution

- Supports TVLogic Color Calibration Utility for proper color alignment
- GPI (RJ45)
- Timecode Display
- Waveform/Vectorscope(Y/ Cb/Cr, Blue Only/Mono Wide Type, Line Waveform)
- Range Error
- Marker
- User Aspect

- HDMI to HD-SDI converted output
- H/V Delay
- UMD support (ANC, Manual, Dynamic & User)
- Closed Caption: CEA- 608/708 (SDI), Line 21, ANC
- Monitor control using RS422
- Aluminum Die-cast Case
- Focus Assist
- Built-in V-Mount

SPECIFICATION

LCD	
Size	9"
Resolution	1920 x 1080 (16 : 9)
Pixel Pitch	0.1035mm
Color Depth	16.7M (Dithered 8bit)
Viewing Angle (Typ.)	176°(H) / 176°(V)
Luminance (Max.)	400cd/m ² (Typ.)
Contrast Ratio	750:1
Display Area	199(H) x 112(V) mm
Input	
1 X BNC	SDI A/B Channel Input
1 X HDMI	HDMI 1 Input
Output	
1 X BNC	SDI A/B Selected Channel Output (HDMI-to-SDI)
Input Signal	
3G-SDI	2.970Gbps
HD-SDI	1.485Gbps
SD-SDI	270Mbps

HDMI (PC & HDMI Mode)	1080p (23.98/24/25/30/50/59.94/60)/1080i(50/59.94/60)/720p(50/60) 480i(60)/480p(60)/576i(50)/576p(50) 640x480/720x400/800x600/1024x768/1280x768/1280x1024/1366x768
SDI Input Signal Format	
SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-274M	1080i (60 / 59.94 / 50)
	1080p (30/29.97/25/24/24sF/23.98/23.98sF)
SMPTE-296M	720p (60/59.94/50)
SMPTE-260M	1035i (60/59.94)
SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)
2K Format	2048 x 1080p (24/24sF/23.98/23.98sF)
Other Spec	
Audio IN	Embedded Audio / Analog stereo (Phone Jack)
Audio OUT	Analog stereo (Phone Jack) / Internal Speaker (Mixed Mono)
Power	DC 12/24V
Power Consumption (Approx.)	TBD
Operating Temperature	0°C to 45°C (32°F to 113°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Accessory	AC Power Cord / DC Power Adaptor / Camera Mount Support / Handle / Stand

⚠ Specifications may be changed without notice.